

PEAK STYLE

PRODUCT SPECIFICATIONS



Available in 8', 10', 12', 14', 16' and 18' wide — up to 60' long

Also available in finished style.

SKIDS	Treated 2x6 pine — Layers: 2 for lengths up to 22', 3 for 24'-30', 4 for 32' and over.
FLOOR JOISTS	On 16" centers: 2x4 for 8' widths, 2x6 for 10'-16' widths, 2x8 for 18' widths.
FLOORING	5/8" plywood
WALL STUDS	2x4 on 24" centers or less with one dadoes for 1x2 belt rail.
BOTTOM PLATE	2x4
TOP PLATE	2x4
WALL HEIGHT	81" at low point with cathedral ceiling
TRUSSES	2x6 24" O.C. for 8'-12' widths, 2x8 24" O.C. for 14'&16', 2x10 for 18' width
ROOF	Choice of 3/8" osb decking with 30 ga mobile home roof or 29 ga metal with no decking
DOOR	36"x72", 36"x76" or 48"x72" blank mobile home-type with key-in-knob lockset.
WINDOW	30"x27" aluminum frame. Buildings 20' long or less = 1 per building. Buildings over 20' long = 2 per building.
SIDING	29 gauge painted steel or non-painted galvanized installed vertical or horizontal.
LIGHT	1— switch and ceramic light socket (no bulb)

