

# PEAK STYLE

# PRODUCT SPECIFICATIONS

## WITH ROOF OVERHANG



Available in 8', 10', 12', 14', 16', and 18' wide — up to 60' long

Also available in finished style.

<b>SKIDS</b>	Treated 2x6 pine — Layers: 2 for lengths up to 22', 3 for 24'-30', 4 for 32' and over.
<b>FLOOR JOISTS</b>	On 16" centers: 2x4 for 8' widths, 2x6 for 10'-16' widths, 2x8 for 18' widths.
<b>FLOORING</b>	5/8" plywood
<b>WALL STUDS</b>	2x4 on 24" centers or less with one dadoes for 1x2 belt rail.
<b>BOTTOM PLATE</b>	2x4
<b>TOP PLATE</b>	2x4
<b>WALL HEIGHT</b>	81" at low point with cathedral ceiling
<b>TRUSSES</b>	2x6 24" O.C. for 8'-12' widths, 2x8 24" O.C. for 14'&16', 2x10 for 18' width
<b>ROOF</b>	Choice of 3/8" osb decking with 30 ga mobile home roof or 29 ga. metal with no decking
<b>DOOR</b>	36"x72", 36"x76" or 48"x72" blank mobile home-type with key-in-knob lockset.
<b>WINDOW</b>	30"x27" aluminum frame. Buildings 20' long or less = 1 per building. Buildings over 20' long = 2 per building.
<b>SIDING</b>	29 gauge painted steel or non-painted galvanized installed vertical or horizontal.
<b>LIGHT</b>	1— switch and ceramic light socket (no bulb)

